



Overseeder Agri Compact

Economic all-rounder for small, narrow areas



Supplied as standard with

- **Spindle.** Sets the required variable seed dosage quickly, easily and accurately; incl. seed chart on the inside of the lid.
- **Gas strut.** Opens and closes the lid of the seed hopper smoothly.
- **LED lighting.** Clear, bright light ensures safe road transport and clear signals.
- **Mechanical hectare counter.** Registers how many hectares have been sown.
- **Sight glass.** Shows the level in the seed hopper.

Added value options

- **Heavy cast iron packer ring roller.** Inhibits growth of problem grasses and promotes the shoot formation of good grasses.
- **Scraper for packer ring roller.** Ensures each moveable packer ring stays clean. Suitable for working in wet, heavy conditions.
- **Platform.** Helps fill the machine safely.
- **Demountable hill plates.** Ensures good seed dosage on steep slopes.
- **Stone protection.** Prevents stones, clods and crop residues entering and blocking the discs.
- **Second hectare counter.** Registers how many hectares have been sown. This second counter closes with a lid and lock. Useful if overseeder is rented out.

Technical specifications

- Suitable for: grassland, fruit growing, viticulture
- Seed dosage: 3 - 190 kg per hectare (continuously adjustable)
- Sowing depth: 0-25 mm
- Working speed: 10-12 km per hour
- Discs: 2x sharp cutting discs Ø 406 mm and maintenance-free bearings
- Element: 11 cm progressive coil spring
- Turf guard: adjustable
- Pressure roller: 100-220 litres; height adjustable and refillable
- Calibration: calibration table and calibration tray
- Mounting: 3-point; CAT 2
- Power connection: 12 Volts, 7-pin light connector
- Row distance: 7.5 cm

Typ	Walze	Gewicht	Seed hopper volume	Tractor power	GPS working width	Transport dimensions (lxwxh)
DZ 210.07.5	Smooth	565 kg	100 litre	25 hp	0.97 m	1.31 x 1:15 x 1.23 m
DZ 210.07.5	Packer ring	730 kg	100 litre	40 hp	0.97 m	1.31 x 1:15 x 1.23 m
DZ 214.07.5	Smooth	725 kg	140 litre	30 hp	1.35 m	1.31 x 1:55 x 1.23 m
DZ 214.07.5	Packer ring	990 kg	140 litre	50 hp	1.35 m	1.31 x 1:55 x 1.23 m
DZ 218.07.5	Smooth	890 kg	180 litre	40 hp	1.80 m	1.31 x 1.95 x 1.23 m.
DZ 218.07.5	Packer ring	1.188 kg	180 litre	65 hp	1.80 m	1.31 x 1.95 x 1.23 m
DZ 222.07.5	Smooth	1.015 kg	220 litre	55 hp	2.17 m	1.31 x 2.35 x 1.23 m
DZ 222.07.5	Packer ring	1.420 kg	220 litre	80 hp	2.17 m	1.31 x 2.35 x 1.23 m

Smooth roller compared with packer ring roller

Smooth roller:

- Lighter in weight, but can be filled with water.
- Attractive price-quality ratio.
- Compacts soil and the cut.
- Levels rough surfaces.

Packer ring roller:

- Follows the contours of the field perfectly as the rings (discs) move individually with a height variation of 5 cm.
- Individual discs press the cut from the side to optimally enclose seed in the soil.
- Inhibits growth of problem grasses (with short roots).
- Promotes shoot formation of good grasses.



Your fields, our passion