



Overseeder DZ Agri Twin

Total solution for intensive and large-scale grassland management.



Supplied as standard with

- **Calibration tray.** Handy tool for the calibration test. Easy to store.
- **Gas strut.** Opens and closes the lid of the seed hopper smoothly.
- **LED lighting.** Clear, bright light ensures safe road transport and clear signals.
- **Platform.** Helps fill the machine safely.
- **Digital hectare counter.** Registers how many hectares have been sown.
- **Sight glass.** Shows the level in the seed hopper.
- **Universal dosing roller.** Enables accurate dosing of grass seeds (5-75 kg/ha).
- **Reflective side marker boards/disc guards.** Automatically shields the discs for safe road transport.
- **Folding steps.** For easy filling from the platform.

Added value options

- **Heavy cast iron packer ring roller.** Inhibits growth of problem grasses and promotes the shoot formation of good grasses.
- **Scraper for packer ring roller.** Ensures each moveable packer ring stays clean. Suitable for working in wet, heavy conditions.
- **Electronic Dosing System (EDS).** Dosing rate can be adjusted from the tractor cab, for example in bare patches or headlands. The system includes an electronic sensor that gives a clear acoustic and light signal when the seed hopper is empty.
- **Cam wheels for fine or coarse seed.** Enables small amounts of fine seed or large amounts of coarse seed to be sown.
- **TÜV equipment with LED lights.** Marker boards and lighting approved by German TÜV, incl. registration plate holder with lighting, ensure safe road transport.
- **Stone protection.** Prevents stones, clods and crop residues entering and blocking the discs.
- **Protection cover.** Protects the discs and keeps them clean. Prevents slaking and crusting of elements from the rear.
- **K50 tow bar with 19 mm pin.** To transport a trailer incl. light connector kit.
- **Pre-roller. Compacts the loose soil behind the tractor wheel.** Easy to adjust with the adjustment spindle.

Connections

- 2x double-acting hydraulic valve
- 1x hydraulic pressure-free return
- 12 Volt light connector

Technical specifications

- Suitable for: grassland and hilly conditions
- Seed dosage: 3 - 190 kg per hectare (continuously adjustable)
- Sowing depth: 0-25 mm
- Working speed: 10-12 km per hour
- Hydraulic fan: max. 25 litres , 160 bar
- Discs: 2x sharp cutting discs Ø 406 mm and maintenance-free bearings
- Element: 11 cm progressive coil spring
- Turf guard: adjustable
- Pressure roller: 440-580 litres; height adjustable and refillable
- Calibration: calibration table and calibration tray
- Mounting: 3-point; CAT 3
- Depth adjustment: top link
- Row distance: 7.5 cm

Type	Roller	Weight	Seed hopper volume	Tractor power	GPS working width	Transport dimensions (lxwxh)
DZ 344.07.5	Smooth	2.000 kg	450 litre	125 hp	4.35 m	1.49 x 3.00 x 2.20 m
DZ 344.07.5	Packer ring	3.250 kg	450 litre	150 hp	4.35 m	1.49 x 3.00 x 2.20 m
DZ 358.07.5	Smooth	2.695 kg	450 litre	150 hp	5.70 m	1.49 x 3.00 x 2.90 m
DZ 358.07.5	Packer ring	4.285 kg	450 litre	180 hp	5.70 m	1.49 x 3.00 x 2.90 m

Smooth roller compared with packer ring roller

Smooth roller:

- Lighter in weight, but can be filled with water.
- Attractive price-quality ratio.
- Compacts soil and the cut.
- Levels rough surfaces.

Packer ring roller:

- Follows the contours of the field perfectly as the rings (discs) move individually with a height variation of 5 cm.
- Individual discs press the cut from the side to optimally enclose seed in the soil.
- Inhibits growth of problem grasses (with short roots).
- Promotes shoot formation of good grasses.



Your fields, our passion