

Vredo Overseeders

DZ Sport



Unrivalled capacity and precision

Providing the perfect grass yield in a short amount of time, that's what matters in the overseeding of sport fields and fairways. A strong and green turf is the pursuit of each golf and soccer club for both the amateur and the professionals. This hectare hog, with a working width of 2.2 meters, a row distance of 3.5 cm and a working speed of approximately 16 km/h, quickly provides a the field with new grass seed. The simple handling and maneuverability make sure the seed gets applied at the most important places for a strong turf. The Vredo Sport saves and enriches the old turf with new seed. This gets sown at the correct depth and in the correct amount using, the depth control, which can be adjusted from 0 to 20 mm.

Fitting in every situation

Because of its compact build, it is easy to transport the machine on a trailer and it fits perfectly through the gates of sport fields and golf courses.

The Vredo Sport is available in two versions: as a towed model as well as a three point model. The towed version has a very low ground pressure because of the wide tires, and can be operated with a relatively light tractor. The wheel kit has an unique hydraulic system which follows the ground

perfectly, even on sharp imperfections. The wheel kit has brakes for safe road transport. The three point mounted model is short built and therefore very maneuverable and perfect for sowing in corners and other tight area.

Unique features

The seed dosage of the Vredo Sport is adjustable, so there is never too much or too little little seed being dispersed. You determine the amount of seed, with the help of the practical designed spindle and seed chart, which is equipped with the most common types of grass and mixtures.

The seed gets regulated precisely, through the cam wheel and the bottom flap, from the beginning until the end in all its movements.

Since all the soil conditions and environmental factors like wind and sun are unique, every turf requires its own specific adjustment. With the Vredo Sport this is child's play. With the use of the calibration tray and the extensive seed chart the dosing is exact and very easily adjustable. This robust machine has been built using high quality materials, which makes it an investment for life .



Vredo Sport; "A world class player"
Every season proven on fields worldwide.







Standard new features

A

Spindle

To adjust the quantity of seed released by the machine. With use of the seed chart at the inner side of the lid, this is an easy job.



Gas cylinder

To open and close the lid smoothly after filling the seed tank.



LED lights

Bright light with clear signs of direction and brakes for transport on the road. $\,$

Options



DDS

Dual Depth/Dosage System (DDS), to sow two kinds of seed, in two different dosages at two different depths, in one pass.



Platform

Stable metal standing platform for easy and safe filling of the machine.



Mudguard (towed option)

Robust set of mudguards with the Vredo logo, to keep the machine clean of splashing water and dirt during working activities and road transport. This saves cleaning time.



Tow bar with electric light connection (towed option)

To hook up extra trailers with material or grass seed. Efficiency in logistics!



Second hectare counter

Ideal for machines that will be rented out. Registers the number of hectares precisely, without the user being able to influence it..



Ball coupling

For safe shockproof road transport with maximum movability between the machine and tractor.

Specifications **Vredo** DZ Sport

Seed distribution	Disc diameter	Element	Turf guard	Compaction roller	Size tires	Calibrate
Variable 3 till 390 kg/a	Ø 406 mm	Progressive suspension 0-20mm sow- ing depth	Adjustable	Refillable, height adjustable 220 liter	500/50 R17 lawn profile	Calibrate chart, Calibrating trays

Model	Working width	Row distance	Contents seed hopper	Compaction roller	Dimensions	Weight ex.	Total weight incl. frame/carrier	Required Tractor Power	Depth adjustment
DZ222.035	2,17 m.	3.5 cm	440 I.	220 I.	1,90x2,40x1,23 m.	2000 kg.	2500 kg	90 hp	Top link/roller
DZ222.035T	2,17 m.	3.5 cm	440 I.	220 I.	4,08x2,40x1,23 m.	2580 kg.	3000 kg	85 hp	Hydraulic

www.vredo.com +31 (0) 488 411 254 sales@vredo.com

Dealer:

